

SCHOORAFSTANDEN

CONSTRUCTIEVE OPLOSSINGEN VOOR FLEXIBEL BOUWEN

PREDALCO



Vloerdikte [mm]	Traliehoogte [mm]	Schoorafstand [mm] indien tralies alle 600 mm	Schoorafstand [mm] indien tralies alle 800 mm
150 en kleiner	70	1080	980
160	70	1060	960
	90	1320	1160
170	70	1050	950
	90	1300	1140
180	90	1250	1130
	110	1470	1260
190	90	1230	1110
	110	1450	1230
200	110	1430	1210
	130	1570	1360
210	110	1410	1190
	130	1540	1330
220	130	1510	1310
	150	1630	1410
230	130	1490	1260
	150	1600	1390
240	150	1580	1370
	170	1710	1460
250	150	1550	1350
	170	1660	1440
260	170	1640	1420
	190	1760	1500
270	170	1610	1400
	190	1730	1480
280	190	1710	1460
	210	1800	1540
290	190	1660	1440
	210	1770	1510
300	210	1750	1490
	230	1830	1570
310	210	1730	1470
	230	1810	1550
320	230	1790	1530
	250	1870	1450
330	230	1770	1510
	250	1840	1420
340	250	1820	1390
	270	1640	1230
350	250	1800	1370
	270	1610	1200
360	270	1570	1180
	290	1400	1040
370	270	1540	1160
	290	1370	1020
380	290	1340	1000
	310	1350	1110
390	290	1320	980
	310	1300	1050
400	310	1200	950
	330	1050	900

NOTA: alle maten in mm – breedplaatdikte 50 mm – belasting: eigengewicht vloer + 2,0 kN/m² - maximale doorbuiging van 1/500 x overspanning – vrij opgelegd op 2 steunpunten – het beton dient gestort te worden ter hoogte van de stutten